

Fujitsu recommends Windows.

Data Sheet

FUJITSU ESPRIMO P410 E85+ Desktop PC

Your Immediately Deliverable Office PC

The FUJITSU ESPRIMO P410 microtower PC delivers high-quality computing for your office applications and projects. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use configuration options to meet your specific hardware needs. With its new design it fits perfect into the modern office.

High performance and best price/performance ratio

Cost-effective system for price-conscious customers

- 3rd generation Intel® Core™ i3, Core™ i5, and Core™ i7 processors

Flexibility

Freedom of choice with tailored systems, perfect fit for specific requirements

- Flexible logistic concept - optional customizing program

Reliability

High-quality and functional stability

- Development and production in Europe

Lifecycle

Hardware continuity for long-term projects

- Managed lifecycle up to 12 months



Components

Processor	Intel® Core™ i7-3770 processor (4 Cores / 8 Threads, 3.40 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics 4000) * Intel® Core™ i5-3470 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 2500) * Intel® Core™ i5-3340 processor (4 Cores / 4 Threads, 3.10 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 2500) Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500) Intel® Pentium® processor G2120 (2 Cores / 2 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G2030 (2 Cores / 2 Threads, 3.00 GHz, 3 MB, Intel® HD Graphics) Intel® Celeron® processor G1610 (2 Cores / 2 Threads, 2.60 GHz, 2 MB, Intel® HD Graphics) *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Operating systems	
Operating system	Windows 8 Pro Windows 8 Windows 7 Professional 64-bit Windows 7 Professional 32-bit
Operating system compatible	openSUSE Linux Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM 8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Hard disk drives (internal)	SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch, SED SSD SATA III, 128 GB, 2.5-inch HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch HDD SATA III, 7,200 rpm, 250 GB, 3.5-inch HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch
Graphics	NVIDIA® GeForce® GT630 DisplayPort 2GB FH, 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB FH, 1 GB DP to DVI-D (single link) Adapter Cable ATI Radeon® HD7350 1GB FH, 1 GB
Drives (optional)	BD Triple Writer SATA slim (tray) DVD-ROM DVD Super Multi MultiCard Reader 24in1 USB 2.0 3.5"

**Interface add on cards/components
(optional)**

WLAN III, 802.11g/Draft-n (Windows only, dedicated regions only, not for Indonesia)
WLAN 802.11 a/g/n (2x2), (dedicated regions only, not for Indonesia)
USB 3.0 PCIe x1
Gigabit Ethernet PCIe x1, DS
Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO P410 E85+
Mainboard	
Mainboard type	D3120
Formfactor	µATX
Chipset	Intel® H61
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1,600 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1,000 MBit/s Realtek RTL 8111E
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC663
Audio features	High Definition Audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
Controller functions	Serial ATA II (3 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB 3.0 total	optional
USB front	2
USB rear	4
USB internal	2
VGA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1

Input device / components

	Optical USB wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	3,5" bay can be used for 2,5" drives

Slots

PCI-Express 2.0 x16	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	2 x (190 mm / 7.48 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1,759 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
Graphics features	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL® 1.1 (depending on CPU)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85% 0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=cbab6857-c962-423e-9fa4-0859274833cf

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 3770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) Bystander position
Standard noise operation mode: CPU 50% load	3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: HDD load	3.6 B / 23 dB(A) Bystander; 26 dB(A) Operator position
Standard noise operation mode: Idle mode	3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: ODD load	4.5 B / 31 dB(A) Bystander; 37 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.5 B / 22 dB(A) Bystander; 25 dB(A) Operator position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 425 x 353 mm 6.89 x 16.74 x 13.9 inch
Operating position	Vertical
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO P410
Model	MI4W
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Additional Software




Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Supported standards	DMI PXE WMI

Security	
Physical Security	Kensington Lock support Eye for padlock
System and BIOS Security	Boot sector virus protection Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
Miscellaneous	
Packaging information	
Packaging dimension (mm)	500 x 290 x 540 mm
Packaging dimension (inch)	19.69 x 11.42 x 21.26 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (lbs) Carton	2.8 lbs
Material - Weight (g) EPS / PS	160 g
Material - Weight (lbs) EPS / PS	0.35 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process
Warranty	
Standard Warranty	1 year (depending on country)
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Maintenance and Support Services - the perfect extension	
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	3 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Mouse M440 ECO		Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.	Order Code: S26381-K450-L200
SOUNDSYSTEM DS E2000 Air		The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.	Order Code: S26391-F7128-L600
UC&C USB Headset Stereo H650e		The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.	Order Code: S26391-F7139-L10

Busylight UC Lync

Boost communication and productivity in the office with the Busylight. The genius of this device is that it both advertises your present working state and promotes the use of Lync, making your office more efficient. Perfect for the work environment in open-plan offices, the Busylight makes users feel comfortable with Lync's features and eases the transition from traditional office internal telephone systems.

Order Code:
S26391-F7139-L30

HS E2000 Communicator Headset

The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code:
S26391-F7139-L5

Keyboard KBPC PX ECO

Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1** (**:
country specific variation)

Keyboard KB900

The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU ESPRIMO P410 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU ESPRIMO P410 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2014-07-09 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions