



**CR35wiNG**

**Future-ready Security with Wi-Fi Access Point for SOHO/ROBO networks**

Data Sheet

CR35wiNG is the Next-Generation Unified Threat Management appliance with Wi-Fi access points that offer “the fastest UTM’s made for SMBs” to small offices with high performance security over WLAN. CR35wiNG appliances come with 3x3 MIMO technology that greatly enhances wireless range and performance. It supports 802.11a/b/g/n wireless standards. Combined with security over wired networks offered by its range of UTM appliances, Cyberoam enables organizations to overcome the physical limitations of securely accessing network resources and offers more user flexibility, user productivity and lower network ownership costs.

The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks.


Cyberoam’s Layer 8 technology that treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack, works even in WLAN environments, to allow Identity-based security policies in dynamic IP environment.

**The ‘Next-Generation’ UTM Series for SOHO:**


Faster performance, broader coverage with 3x3 MIMO Technology



Cyberoam’s **Layer 8 Technology** treats “User Identity” as the 8th Layer in the protocol stack



Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies



**Cyberoam UTM features assure Security, Connectivity, Productivity**

**Security**

**Network Security**

- Firewall
- Intrusion Prevention System
- Web Application Firewall
- Wireless Security

**Content Security**

- Anti-Virus/Anti-Spyware
- Anti-Spam (Inbound/Outbound)
- HTTPS/SSL Content Security

**Administrative Security**

- Next-Gen UI
- iView- Logging & Reporting



**Connectivity**

**Business Continuity**

- Multiple Link Management

**Network Availability**

- VPN
- 3G/4G/WiMAX Connectivity

**Future-ready Connectivity**

- “IPv6 Ready” Gold Logo



**Productivity**

**Employee Productivity**

- Content Filtering
- Instant Messaging Archiving & Controls

**IT Resource Optimization**

- Bandwidth Management
- Traffic Discovery
- Application Visibility & Control

**Administrator Productivity**

- Next-Gen UI



## Interfaces

Copper GbE Ports	6
Configurable	
Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45/DB9)	1
USB Ports	2

## Built-in Wireless LAN

Wireless Standards	IEEE 802.11 a/b/g/n (WEP, WPA, WPA2, 802.11i, TKIP, AES, PSK)
--------------------	---

Antenna	Detachable 3x3 MIMO
---------	---------------------

Access Points	Up to 8 bssid
---------------	---------------

Transmit Power (EIRP)	11n HT40 : +15dBm 11b CCK: +15dBm 11g OFDM: +15dBm
-----------------------	--

Receiver Sensitivity	-68dBm at 300Mbps -70dBm at 54Mbps -88dBm at 6Mbps
----------------------	--

Frequency Range	2.412 GHz - 2.472 GHz 5.200 GHz - 5.825 GHz
-----------------	--

Number of Selectable Channels	USA (FCC) - 11 channels, EU (ETSI) / Japan (TELEC) - 13 channels
-------------------------------	---

Data Rate	802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11b: 1, 2, 5.5, 11Mbps 802.11n: up to 450Mbps
-----------	---

## System Performance\*

Firewall Throughput (UDP)	2,300 (Mbps)
Firewall Throughput (TCP)	2,000 (Mbps)
New sessions/second	12,000
Concurrent sessions	350,000
IPSec VPN Throughput	250 (Mbps)
No. of IPSec Tunnels	150
SSL VPN Throughput	100 (Mbps)
WAF Protected Throughput	150 (Mbps)
Anti-Virus Throughput	525 (Mbps)
IPS Throughput	350 (Mbps)
UTM Throughput	210 (Mbps)

## Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
- UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
- Layer 7 (Application) Control & Visibility
- Access Scheduling
- Policy based Source & Destination NAT
- H.323, SIP NAT Traversal
- 802.1q VLAN Support
- DoS & DDoS Attack prevention
- MAC & IP-MAC filtering and Spoof prevention

## Gateway Anti-Virus & Anti-Spyware

- Virus, Worm, Trojan Detection & Removal
- Spyware, Malware, Phishing protection
- Automatic virus signature database update
- Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning
- Scan and deliver by file size
- Block by file types
- Add disclaimer/signature

## Gateway Anti-Spam

- Inbound/Outbound Scanning
- Real-time Blacklist (RBL), MIME header check
- Filter based on message header, size, sender, recipient
- Subject line tagging
- IP address Black list/White list
- Redirect Spam mails to dedicated email address
- Image-based Spam filtering using RPD Technology
- Zero hour Virus Outbreak Protection
- IP Reputation-based Spam filtering

## Intrusion Prevention System

- Signatures: Default (4500+), Custom
- IPS Policies: Multiple, Custom
- User-based policy creation
- Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection
- DDoS attack prevention
- SCADA-aware IPS with pre-defined category for ICS and SCADA signatures

## Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block Java Applets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

## Application Filtering

- Inbuilt Application Category Database
- 2,000+ Applications Supported
- Schedule-based access control
- Block
  - Proxy and Tunnel
  - File Transfer
  - Social Networking
  - Streaming Media
  - Storage and Backup
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility
- Securing SCADA Networks
  - SCADA/ICS Signature-based Filtering for Protocols - Modbus, DNP3, IEC, Bacnet, Omron FINS, Secure DNP3, Longtalk
  - Control various Commands and Functions

## Web Application Firewall

- Positive Protection model
- Unique "Intuitive Website Flow Detector" technology
- Protection against SQL Injections, Cross-site Scripting (XSS), Session Hijacking, URL Tampering, Cookie Poisoning
- Support for HTTP 0.9/1.0/1.1
- Extensive Logging & Reporting

## Virtual Private Network

- IPSec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPSec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

## SSL VPN

- TCP&UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSL VPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP-based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

## Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Content Alerts

## Wireless WAN

- USB port 3G/4G and Wimax Support
- Primary WAN link
- WAN Backup link

## Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

## User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

## Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3GModem failover
- WRR based load balancing
- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy
- Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- "IPv6 Ready" Gold Logo

## Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- NTP Support

## User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003 Terminal Services and Citrix XenApp
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

## Logging/Monitoring

- Graphical real-time and historical monitoring
- Email notification of reports, viruses and attacks
- Syslog support
- Log Viewer - IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

## On-Appliance Cyberoam-iView Reporting

- Integrated Web-based Reporting tool - Cyberoam-iView
- 1000+ drilldown reports
- 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Security, Spam, Virus, Traffic, Policy violations, VPN, Search Engine keywords
- Multi-format reports - tabular, graphical
- Exportable formats - PDF, Excel
- Automated Report Scheduling

## IPSec VPN Client\*\*

- Inter-operability with major IPSec VPN Gateways
- Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

## Certification

- Common Criteria - EAL4+
- ICSA Firewall - Corporate
- Checkmark UTM Level 5 Certification
- VPNC - Basic and AES interoperability
- "IPv6 Ready" Gold Logo

## Hardware Specifications

Memory	2GB
Compact Flash	2GB
HDD	250GB or higher

## Compliance

- CE
- FCC

## Dimensions

H x W x D (inches)	1.7 x 6 x 9.1
H x W x D (cms)	4.4 x 15.3 x 23.2
Weight	2.3kg, 5.07 lbs

## Power

Input Voltage	100-240 VAC
Consumption	47.8W
Total Heat Dissipation (BTU)	163

## Environmental

Operating Temperature	0 to 40 °C
Storage Temperature	-25 to 75 °C
Relative Humidity (Non condensing)	10 to 90%

\*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

\*\*Additional purchase required.